

Product details

CLIP top standard hinge 107°, horizontal, with spring, Boss: INSERTA



Part number	75T1590B
Item number	06779663
Colour / finish	Nickel plated
Packaging quantity	250
Weight per 1,000 Pcs in kg	94
EAN code	9002617642049
UPC code	

Technical attributes

applicationstandard hingeCrankinghorizontalOpening angle107Colsing mechanismwith springhinge variantfor BLUMOTION 973ABoss materialSteel bossBoss materialNickel platedBoss assemblyNiSERTAFlange kingth65Flange height7Gametre for positioning peg drilling8diametre of positioning peg drilling5diametre of positioning peg drillings9.5boss drilling depth11.35boss drilling distance6arm materialSteelarm material3arm material12collision measurement (hinge arm height)21Fixed dimenter (hinge arm height)11Fixed dimenter (hinge arm height)12Fixed dimenter (hinge arm height)12Collision measurement (hinge arm height)12Fixed dimenter (hinge arm height)14Fixed dimenter (hinge arm height)12Fixed dimenter (hinge arm height)13Fixed dimenter (hinge arm height)12Fixed dimenter (hinge arm height)13Fixed dimenter (hinge arm height)14Fixed dimenter (hinge arm height)14Fixed dimenter (hinge arm height)15Fixed dimenter (hinge arm height)15<	Attribute	Value
Open open signage107Closing mechanismwith springLinge variantFor LUMOTION 973ABoss materialSteel boosBoss materialNickel platedBoss materialNickel platedBoss assemblyINSERTAFlange width65Flange length7Gametre hinge boos drilling35diametre of positioning peg drilling8.diametre of positioning peg drilling9.5booss depth1.35booss depth3.booss depth3.Minnum drilling distance6arm materialSteel Jaccenteric Destioning peg noticinarm finishSteel Jaccenteric Destion peg drillingcollision neasurement (hinge arm height)11Steel Jaccenteric Destion peg drilling11per of side adjustment11type of side adjustment11type of side adjustment11type of side adjustment12Steel depth12Steel depth12Fixed dimension / factory setting11Steel adjustment12Steel adjustment12<	application	standard hinge
Closing mechanismwith springhinge variantfor BLUMOTION 973ABoss materialSteel bossboss finishNickel platedBoss assemblyINSERTABrange vindth65Flange height7diametre hinge boss drilling35diametre of positioning peg drilling8distance of positioning peg position9.5distance of positioning peg option9.5boss drilling depth1.35boss drilling distance3arm material3arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)11fixed dijustment1.4fixed dijustment11fixed dijustment11fixed dijustment0.1fixed dijustment1.4fixed dijustment1.4fixed dijustment0.1fixed dijustment0.1 </td <td>Cranking</td> <td>horizontal</td>	Cranking	horizontal
hingfor BLUMOTION 973ABoss materialSteel bossboss finishNickel platedBoss assemblyINSERTABlange width65Blange length23Flange height7diametre finisp boss drilling8diametre of positioning peg drilling8exceentric positioning peg drilling9.5boss drilling depth1.35boss drilling distance3boss drilling distance3arm materialSteelarm materialSteelcollision measurement (hinge arm height)11Fixed dimension / factory setting11Steed distante11Steed distante11Fixed dimension / factory setting11Fixed dimension / factory setting11Steed distante11Steed distante11Steed distante11Collision measurement (hinge arm height)11Fixed dimension / factory setting11Steed distante12Steed distantent12Steed distantent12Steed distantent11Steed distantent11Steed distantent12Steed distantent12Steed distantent12Steed distantent12Steed distantent13Steed distantent13Steed distantent13Steed distantent14Steed distantent14Steed distantent14Steed dista	Opening angle	107
Bos materialSteel bossboss finishNickel platedBoss assemblyINSERTAFlange width65Flange length23flange boss drilling55diametre fo positioning peg drilling8diametre of positioning peg drilling8exccentric positioning peg drillings9.5distance of position peg drillings11.35boss depth12Maximum drilling distance6Maximum drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)11type of dept adjustment11type of side adjustment11type of dept adjustment11type of dept adjustment11type of dept adjustment11type of dept adjustment12Side adjustment11type of dept adjustment11type of dept adjustment12Side adjustment12type of dept adjustment13type of dept adjustment13type of dept adjustment14type of dept adjustment14type of dept adjustment15type of dept adjustment15 <td< td=""><td>Closing mechanism</td><td>with spring</td></td<>	Closing mechanism	with spring
boss finishNickel platedBoss assemblyINSERTAFlange width65Flange length23Flange height7diametre hinge boss drilling8exccentric positioning peg drillings8exccentric positioning peg drillings9.5distance of position peg drillings13.5boss depth12Minimum drilling distance3marterialStellarm materialStellcollision measurement (hinge arm height)11Fixed dimenterion (factory setting11Side adjustment11type of side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment12Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment12Side adjustment12Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Side adjustment12Side adjustment11Side adjustment12Side adjustment12Side adjustment15Side adjustment15Side adjustment15Side adj	hinge variant	for BLUMOTION 973A
Bos assemblyINSERTAFlange width65Flange length33Flange height7diametre hinge boss drilling35diametre of positioning peg drilling9.5distance of positioning peg position9.5distance of position peg drillings1.35boss depth1.35boss depth3Minimum drilling distance6arm materialStellarm finishNickel platedcollision measurement (hinge arm height)11Side adjustment11Side adjustment11Side adjustment11Side adjustment11Gig di	Boss material	Steel boss
Flange width65Flange length33Flange height7diametre hinge boss drilling35diametre of positioning peg drilling8excentric positioning peg position9.5distance of position peg drillings45boss depth11.35boss drilling distance3Maximum drilling distance6arm materialSteelarm finishSteelcollision measurement (hinge arm height)1Fixed dimension / factory setting11.4Yee of side adjustmentYei screwSide adjustment1.4Side adjustment1.4Side adjustment9.1Side adjustment9.1Side adjustment1.4Side adjustment1.4Side adjustment1.4Side adjustment9.1Side adjustment1.4Side adjustment1.4Side adjustment1.4Side adjustment1.4Side adjustment1.4Side adjustment1.4Side adjustment1.5Gap1.5Sim adjustment1.5Sim adjustment1.5S	boss finish	Nickel plated
Flange length23Flange height7diametre hinge boss drilling35diametre of positioning peg drilling8exccentric positioning peg position9.5distance of position peg drillings45boss depth11.35boss drilling distance3Minimum drilling distance6arm materialSteelcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentVith screwSide adjustmentVith screwSide adjustment5Opeth adjustment5Gap1.5Tim package1.5	Boss assembly	INSERTA
Flage height7diametre hinge boss drilling35diametre of positioning peg drilling8exceentric positioning peg position9.5distance of position peg drillings45boss depth12boss drilling depth3Maximum drilling distance6arm materialSteelcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentVith screwSide adjustment	Flange width	65
diametre hinge boss drilling35diametre of positioning peg drilling8exccentric positioning peg position9.5distance of position peg drillings45boss depth11.35boss drilling depth3Minimu drilling distance6arm materialSteelcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentVith screwSide adjustmentvith spral screwtype of depth adjustmentpuss drilling sizeGap1.5type package1.5	Flange length	23
diametre of positioning peg drilling8exccentric positioning peg position9.5distance of position peg drillings45boss depth11.35boss drilling depth2Minimu drilling distance3arm materialSteelarm finishNickel platedcollison measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentYith screwSide adjustmentVith screwtype of depth adjustmentplus 3/minus 2 mmGap1.5tem package1piece	Flange height	7
exccentric positioning peg position9.5distance of position peg drillings45boss depth11.35boss drilling depth12Minimu drilling distance3Maximun drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentVith screwSide adjustment4/- 2 mmtype of depth adjustmentplus 3/minus 2 mmGap1.5tem package1 piece	diametre hinge boss drilling	35
distance of position peg drillings45boss depth11.35boss drilling depth12Minimu drilling distance3Maximu drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentVith screwSide adjustmentVith screwtype of depth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	diametre of positioning peg drilling	8
boss depth11.35boss drilling depth12Minimum drilling distance3Maximum drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	exccentric positioning peg position	9.5
boss drilling depth12Minimum drilling distance3Maximum drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment-/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustment1.5Gap1.5Item package1 piece	distance of position peg drillings	45
Minimum drilling distance3Maximum drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	boss depth	11.35
Maximum drilling distance6arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	boss drilling depth	12
arm materialSteelarm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	Minimum drilling distance	3
arm finishNickel platedcollision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	Maximum drilling distance	6
collision measurement (hinge arm height)21Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	arm material	Steel
Fixed dimension / factory setting11type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	arm finish	Nickel plated
type of side adjustmentWith screwSide adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	collision measurement (hinge arm height)	21
Side adjustment+/- 2 mmtype of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	Fixed dimension / factory setting	11
type of depth adjustmentconvenient with spiral screwDepth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	type of side adjustment	With screw
Depth adjustmentplus 3/minus 2 mmGap1.5Item package1 piece	Side adjustment	+/- 2 mm
Gap1.5Item package1 piece	type of depth adjustment	convenient with spiral screw
Item package 1 piece	Depth adjustment	plus 3/minus 2 mm
	Gap	1.5
packaging industrial packing	Item package	1 piece
	packaging	industrial packing

© Julius Blum GmbH / Legal terms and conditions: The information provided is not binding and Julius Blum GmbH assumes no legal responsibility for it. Julius Blum GmbH makes no warranty for inaccurate or erroneous data.