



Benefits

- Easy to use and install
- High efficiency
- Integrated JB4 distributor ports

Key Features

- Depth of 16mm
- Available as 6W/15W/30W
- 2m mains cable included
- Short circuit & overload protection
- Surge and thermal protection

Technical Specification

Drivers	6W	15W	30W
Rated Input Voltage (Vac)	220-240	220-240	220-240
Input Voltage Range (Vac)	198-264	198-264	198-264
Frequency (Hz)	50/60 ± 3%	50/60 ± 3%	50/60 ± 3%
Output Voltage (V)	24 ± 5%	24 ± 5%	24 ± 5%
Output Current (A)	0.250	0.625	1.25
Short Circuit Protection	Yes	Yes	Yes
Overload Protection	Yes	Yes	Yes
Thermal Protection	Yes	Yes	Yes
Surge Protection	Yes	Yes	Yes
Operating Temperature	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C
Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH
Mains Cable Length (M)	2	2	2
Number of JB4 Ports	4	6	6

Product Overview

Measuring at only 16mm in depth, the low-profile driver is a discreet solution that can be hidden away easily during installation.

The driver features integrated JB4 ports rather than a traditional distribution block, which streamlines the design and reduces unnecessary material.

Protected from short-circuiting, overloading and electrical surge, the driver is a safe solution ideal for many applications.

Mechanical Specification

Product	Dimension (mm) L X W X D	Weight (grams)	IP Rating
SE490950	95 X 48 X 16.5	52	20
SE491950	120 X 48 X 16.5	68	20
SE492950	158 X 56 X 16.5	116	20

Order Codes

Description	Order Code	Carton (QTY)
Low Profile Driver 6W	SE490950	50
Low Profile Driver 15W	SE491950	50
Low Profile Driver 30W	SE492950	50