

Technical Specification



Product Code: VPSC722GY Description: 20A Ingot Double Pole Plate Switch





General Information

Plate Dimensions (mm) 88 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 91 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian

Finish Satin Chrome

Insert Colour Grey
Gasket Colour Grey

Materials Front Plate: Stainless Steel Insert & Housing: Urea

Switch Cover: Stainless Steel Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5

Double Pole Switch Yes
Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 60669-1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

